



1810-018A - BLUE STEEL

Mix N' Match Color Collection

100 % acrylic latex paint, interior, eggshell finish

Type	100 % acrylic
Gloss level	8-12 % (60°), 15-25 % (85°)
Finish	Eggshell
Viscosity	95-105 K.U
Coverage	107 to 150 ft ² /L (10 to 14m ² /L)
Thinner / cleaner	Water
Size	1 gallon (3.78 liters)
Drying time	To touch: 30 to 60 minutes ¹ To reapply: 4 to 6 hours
Concentration of solids	By volume: 30 to 35 % By weight: 40 to 50 %
VOCs	<75 g/l

Colors	Pre-mix color
--------	---------------

	1810 - 010A	JUST WHITE*
	1810 - 011A	SERENITY WHITE
	1810 - 012A	BARELY YELLOW
	1810 - 013A	MUST-HAVE BLUE
	1810 - 014A	PERFECT NATURAL*
	1810 - 015A	INFINITE GRAY
	1810 - 016A	LAZY SUNDAY GRAY
	1810 - 017A	SWEET PISTACHIO
	1810 - 018A	BLUE STEEL
	1810 - 019A	COLD MARBLE
	1810 - 020A	MODERN STONE*
	1810 - 021A	DARK LICHEN
	1810 - 022A	NIGHT SKY
	1810 - 023A	CHARISMATIC PINK
	1810 - 024A	CHEERS!
	1810 - 025A	VINTAGE LEATHER
	1810 - 026A	BLACK NOVEL
	1810 - 027A	GOLDEN MUSTARD
	1810 - 028A	BOREAL GREEN
	1810 - 029A	DEEP SEA BLUE
	1810 - 030A	VIBRANT RED
	1810 - 031A	RASPBERRY WINE

Description

Premium eggshell finish paint with low volatile organic compound (VOCs) emissions. It contains no lead or mercury. It is super adherent, opaque, does not turn yellow, does not splatter and has light odour. This paint is ideal for walls with surface irregularities. It is very washable and scrub resistant.

Application

Shake the container well before applying the paint. Use a spatula to stir all the way to the bottom of the container. Apply with a synthetic fibre brush (polyester, nylon) and a good quality lint-free roller 0.5" (10 mm). For spray gun application, it is important to dilute the product 10-15 % with water to obtain a uniform application. Never apply below 50 °F (10 °C) and above 90 °F (32 °C). Humidity level should be lower than 50 %. Ventilate the room well. Two coats should be applied for best product performance.

Storage

Keep in a dry, well-ventilated place at a moderate temperature (about 68 °F (20°C). Avoid freezing.

* Also available in Pearl finish, ultra-washable. Ideal for doors & frames.

Consult your municipality for proper disposal of leftover product. Keep out of the reach of children.

Warning

Keep from freezing.

Before using this product, consult its Material Safety Data Sheet for the Use of Protective Equipment (Section 8), the Preventive Measures (Section 7) and Emergency First Aid Procedures (Section 4). The data mentioned above is provided by Laurentide Paint inc. for information purposes only and do not constitute in any way a representation, promise or warranty as to the use, duration or quality of the product. The identified product must be used in strict accordance with the specifications mentioned and any other instructions, warnings or guidelines issued by Laurentide Paint inc.

MIX N'MATCH™

Pre-mixed Color Collection
by Laurentide Paint

Laurentide Paint 



1810-018A - BLUE STEEL Mix N' Match Color Collection

100 % acrylic latex paint, interior, eggshell finish

Care instructions

It is best to use a soft cloth or sponge and a mild household soap. Do not use abrasive cleaners. Rinse off soap residue thoroughly. To achieve full performance of this paint wait at least 3-4 weeks before doing a first wash.

Surface preparation

Surface preparation is paramount and the final success of the project depends on it. All surfaces must be clean, dry and free of all traces of contaminants, mould and peeling paint. High gloss surfaces should be sanded to allow better adhesion of the paint. Remove old, peeling paint. Thoroughly clean the surface to be painted with a trisodium phosphate solution (TSP). Rinse well and leave to dry.

- **Bare wood:** Apply a bleed-proof latex primer for this purpose (pine, spruce, maple). It is important to seal the knots well. Some woods require the use of a product such as than Shellac on the knots.
- **New gypsum:** The plaster must be completely dry and clean before applying the paint. Apply the primer-sealer 1840-05A Prime3.
- **Previously latex-painted surfaces:** Apply a coat of latex primer 1840-05A Prime3.

- **Previously alkyd-painted surfaces:** If the existing alkyd coat has a matte finish, apply the latex primer 1840-05A Prime3, but if the finish is glossy, sand the surface to allow the latex primer to adhere.
- **New concrete and masonry:** Concrete must be completely dry before applying paint. Clean with muriatic acid and rinse well with water. Apply a coat of latex primer 1840-05A Prime3.
- **Metals:** Prepare the surface with a primer for metal, then apply paint according to application instructions.

Note: Do not use this paint on floors.

- ¹ Drying may take longer in cold and humid conditions.

For more information and ideas, please contact our customer service or visit our stores/distributors. You can also visit our website at mixnmatchpaint.com or write to us at info@laurentidepaint.com.

Before using this product, consult its Material Safety Data Sheet for the Use of Protective Equipment (Section 8), the Preventive Measures (Section 7) and Emergency First Aid Procedures (Section 4). The data mentioned above is provided by Laurentide Paint inc. for information purposes only and do not constitute in any way a representation, promise or warranty as to the use, duration or quality of the product. The identified product must be used in strict accordance with the specifications mentioned and any other instructions, warnings or guidelines issued by Laurentide Paint inc.

SAFETY DATA SHEET

MIX N'MATCH Eggshell Finish BLUE STEEL

Section 1. Identification

Product identifier : MIX N'MATCH Eggshell Finish BLUE STEEL
Product code : 1810-018A
Other means of identification : Not available.
Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Not applicable.

Supplier's details : Peinture Laurentide
4660 boulevard de Shawinigan-sud
Shawinigan
G9N 6T5
Tel: 1-800-567-9481
Fax: 1-800-641-0392

Emergency telephone number (with hours of operation) : CANUTEC (613) 996-6666

Section 2. Hazard identification

Classification of the substance or mixture : SKIN SENSITIZATION - Category 1
CARCINOGENICITY - Category 2

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : May cause an allergic skin reaction.
Suspected of causing cancer.

Precautionary statements

General : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

Prevention : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear protective clothing. Wear eye or face protection. Avoid breathing vapor. Contaminated work clothing should not be allowed out of the workplace.

Response : IF exposed or concerned: Get medical attention. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical attention.

Storage : Store locked up.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements : Percentage of the mixture consisting of ingredient(s) of unknown oral toxicity: 17.9%
Percentage of the mixture consisting of ingredient(s) of unknown dermal toxicity: 27.4%
Percentage of the mixture consisting of ingredient(s) of unknown inhalation toxicity: 56.6%

Section 3. Composition/information on ingredients

Substance/mixture : Mixture
Other means of identification : Not available.

Ingredient name	% (w/w)	CAS number
Dioxyde de titane	10 - 30	13463-67-7
Nepheline syenite	1 - 5	37244-96-5
Poly(oxy-1,2-ethanediyl), α -hydro- ω -hydroxy- Ethane-1,2-diol, ethoxylated	0.5 - 1.5	25322-68-3
Broad-spectrum bactericide and fungicide	0.1 - 1	-
mineral rheological agent	0.1 - 1	-

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.

Section 4. First-aid measures

- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

Specific hazards arising from the chemical : In a fire or if heated, a pressure increase will occur and the container may burst.

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
metal oxide/oxides

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Section 6. Accidental release measures

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Titanium dioxide	<p>CA British Columbia Provincial (Canada, 6/2017). TWA: 3 mg/m³ 8 hours. Form: Respirable dust TWA: 10 mg/m³ 8 hours. Form: Total dust</p> <p>CA Quebec Provincial (Canada, 1/2014). TWA_{EV}: 10 mg/m³ 8 hours. Form: Total dust.</p> <p>CA Alberta Provincial (Canada, 4/2009). 8 hrs OEL: 10 mg/m³ 8 hours.</p> <p>CA Ontario Provincial (Canada, 1/2018). TWA: 10 mg/m³ 8 hours.</p> <p>CA Saskatchewan Provincial (Canada, 7/2013). STEL: 20 mg/m³ 15 minutes.</p>

Section 8. Exposure controls/personal protection

Nepheline syenite

TWA: 10 mg/m³ 8 hours.

CA Ontario Provincial (Canada, 1/2018).
TWA: 10 mg/m³ 8 hours. Form: Total dust

- Appropriate engineering controls** : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : BLUE STEEL
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : Not available.
- Melting point** : Not available.
- Boiling point** : Not available.
- Flash point** : Closed cup: Not applicable.
- Evaporation rate** : Not available.

Section 9. Physical and chemical properties

Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Not available.
Vapor pressure	: Not available.
Vapor density	: Not available.
Relative density	: 1.212
Solubility	: Not available.
Solubility in water	: Not available.
Partition coefficient: n-octanol/water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Not available.
Flow time (ISO 2431)	: Not available.

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Titanium dioxide Broad-spectrum bactericide and fungicide	LC50 Inhalation Dusts and mists	Rat	>6.8 mg/l	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat - Female	1009 to 3950 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium dioxide	Skin - Mild irritant	Human	-	72 hours 300 Micrograms Intermittent	-
Broad-spectrum bactericide and fungicide	Skin - Mild irritant	Rabbit	-	-	-
	Eyes - Cornea opacity	Rabbit	59	-	21 days

Sensitization

Not available.

Mutagenicity

Section 11. Toxicological information

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Pigment dispersion	Category 3	Not applicable.	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure : Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.
Inhalation : No known significant effects or critical hazards.
Skin contact : May cause an allergic skin reaction.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : Adverse symptoms may include the following:
irritation
redness
Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

Section 11. Toxicological information

Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Titanium dioxide	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 6.5 mg/l Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 >1000000 µg/l Marine water	Fish - Fundulus heteroclitus	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	TDG Classification	DOT Classification	ADR/RID	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	-	-	-	-

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to Annex II of MARPOL and the IBC Code : Not available.

Section 15. Regulatory information

Canadian lists

Canadian NPRI : None of the components are listed.

CEPA Toxic substances : None of the components are listed.

Canada inventory : Not determined.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia : Not determined.

China : Not determined.

Europe : Not determined.

Japan : **Japan inventory (ENCS):** Not determined.
Japan inventory (ISHL): Not determined.

Malaysia : Not determined.

Section 15. Regulatory information

New Zealand	: Not determined.
Philippines	: Not determined.
Republic of Korea	: Not determined.
Taiwan	: Not determined.
Turkey	: Not determined.
United States	: All components are listed or exempted.

Section 16. Other information

History

Date of printing	: 2020-12-15
Date of issue/Date of revision	: 2020-12-15
Date of previous issue	: 2020-12-15
Version	: 0.04

Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations HPR = Hazardous Products Regulations
-----------------------------	--

Procedure used to derive the classification

Classification	Justification
SKIN SENSITIZATION - Category 1	Calculation method
CARCINOGENICITY - Category 2	Calculation method

References	: Not available.
-------------------	------------------

✔ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.