



## 1810-033AC - ABSOLUTE BLACK

### Mix N'Match Colour Collection

100 % acrylic latex paint, interior, eggshell finish

Type	100 % acrylic
Gloss level	8-12 % (60°), 15-25 % (85°)
Finish	Eggshell
Viscosity	95-105 K.U
Coverage	10-14 m <sup>2</sup> /L (107 to 150 ft <sup>2</sup> /L)
Thinner / cleaner	Water
Size	3.78 liters (1 gallon)
Drying time	To touch: 30 to 60 minutes <sup>1</sup> To reapply: 4 to 6 hours
Concentration of solids	By volume: 30 to 35 % By weight: 40 to 50 %
VOCs	< 75 g/l

Colours	Pre-mix colour
 1810 - 010AC	JUST WHITE*
 1810 - 011AC	SERENITY WHITE*
 1810 - 012AC	BARELY YELLOW
 1810 - 013AC	MUST-HAVE BLUE
 1810 - 014AC	PERFECT NEUTRAL*
 1810 - 015AC	INFINITE GREY
 1810 - 016AC	LAZY SUNDAY GREY
 1810 - 017AC	SWEET PISTACHIO
 1810 - 018AC	BLUE STEEL
 1810 - 019AC	COLD MARBLE
 1810 - 020AC	MODERN STONE*
 1810 - 021AC	DARK LICHEN
 1810 - 022AC	NIGHT SKY
 1810 - 023AC	CHARISMATIC PINK
 1810 - 024AC	CHEERS!
 1810 - 025AC	VINTAGE LEATHER
 1810 - 026AC	BLACK NOVEL*
 1810 - 027AC	GOLDEN MUSTARD
 1810 - 028AC	BOREAL GREEN
 1810 - 029AC	DEEP SEA BLUE
 1810 - 030AC	VIBRANT RED
 1810 - 031AC	RASPBERRY WINE
 1810 - 032AC	SPARKLING WHITE*
 1810 - 033AC	ABSOLUTE BLACK*

#### Description

Premium eggshell finish paint with low volatile organic compound (VOCs) emissions. It contains no lead or mercury. It is super adherent, opaque, does not turn yellow, does not splatter and has light odour. This paint is ideal for walls with surface irregularities. It is very washable and scrub resistant.

#### Application

Shake the container well before applying the paint. Use a spatula to stir all the way to the bottom of the container. Apply with a synthetic fibre brush (polyester, nylon) and a good quality lint-free roller 10 mm (0.5"). For spray gun application, it is important to dilute the product 10-15 % with water to obtain a uniform application. Never apply below 10 °C (50 °F) and above 32 °C (90 °F). Humidity level should be lower than 50 %. Ventilate the room well. Two coats should be applied for best product performance.

#### Storage

Keep in a dry, well-ventilated place at a moderate temperature (about 20 °C (68 °F)). Avoid freezing.

\* Also available in pearl finish, ultra-washable. Ideal for doors & frames.

**Consult your municipality for proper disposal of leftover product. Keep out of the reach of children.**

#### Warning

Keep from freezing.

# MIX N'MATCH™

Pre-mixed Colour Collection  
by Laurentide Paint

Laurentide Paint 



## 1810-033AC - ABSOLUTE BLACK

### Mix N'Match Colour Collection

100 % acrylic latex paint, interior, eggshell finish

#### Care instructions

It is best to use a soft cloth or sponge and a mild household soap. Do not use abrasive cleaners. Rinse off soap residue thoroughly. To achieve full performance of this paint wait at least 3-4 weeks before doing a first wash.

#### Surface preparation

Surface preparation is paramount and the final success of the project depends on it. All surfaces must be clean, dry and free of all traces of contaminants, mould and peeling paint. High gloss surfaces should be sanded to allow better adhesion of the paint. Remove old, peeling paint. Thoroughly clean the surface to be painted with a trisodium phosphate solution (TSP). Rinse well and leave to dry.

- **Bare wood:** Apply a bleed-proof latex primer for this purpose (pine, spruce, maple). It is important to seal the knots well. Some woods require the use of a product such as than Shellac on the knots.
- **New gypsum:** The plaster must be completely dry and clean before applying the paint. Apply the primer-sealer 1840-05AC Prime3.
- **Previously latex-painted surfaces:** Apply a coat of latex primer 1840-05AC Prime3.

- **Previously alkyd-painted surfaces:** If the existing alkyd coat has a matte finish, apply the latex primer 1840-05AC Prime3, but if the finish is glossy, sand the surface to allow the latex primer to adhere.
- **New concrete and masonry:** Concrete must be completely dry before applying paint. Clean with muriatic acid and rinse well with water. Apply a coat of latex primer 1840-05AC Prime3.
- **Metals:** Prepare the surface with a primer for metal, then apply paint according to application instructions.

**Note:** Do not use this paint on floors.

<sup>1</sup> Drying may take longer in cold and humid conditions.

For more information and ideas, please contact our customer service or visit our stores/distributors. You can also visit our website at [premixpaint.com](http://premixpaint.com) or write to us at [info@laurentidepaint.com](mailto:info@laurentidepaint.com).

Before using this product, consult its Material Safety Data Sheet for the Use of Protective Equipment (Section 8), the Preventive Measures (Section 7) and Emergency First Aid Procedures (Section 4). The data mentioned above is provided by Laurentide Paint inc. for information purposes only and do not constitute in any way a representation, promise or warranty as to the use, duration or quality of the product. The identified product must be used in strict accordance with the specifications mentioned and any other instructions, warnings or guidelines issued by Laurentide Paint inc.