



## 1810-033A - ABSOLUTE BLACK

### Mix N'Match Color Collection

100 % acrylic latex paint, interior, eggshell finish

<b>Type</b>	100 % acrylic
<b>Gloss level</b>	8-12 % (60°), 15-25 % (85°)
<b>Finish</b>	Eggshell
<b>Viscosity</b>	95-105 K.U
<b>Coverage</b>	107 to 150 ft <sup>2</sup> /L (10 to 14m <sup>2</sup> /L)
<b>Thinner / cleaner</b>	Water
<b>Size</b>	1 gallon (3.78 liters)
<b>Drying time</b>	To touch: 30 to 60 minutes <sup>1</sup> To reapply: 4 to 6 hours
<b>Concentration of solids</b>	By volume: 30 to 35 % By weight: 40 to 50 %
<b>VOCs</b>	< 75 g/l

Colors	Pre-mix color
 1810 - 010A	JUST WHITE*
 1810 - 011A	SERENITY WHITE*
 1810 - 012A	BARELY YELLOW
 1810 - 013A	MUST-HAVE BLUE
 1810 - 014A	PERFECT NEUTRAL*
 1810 - 015A	INFINITE GRAY
 1810 - 016A	LAZY SUNDAY GRAY
 1810 - 017A	SWEET PISTACHIO
 1810 - 018A	BLUE STEEL
 1810 - 019A	COLD MARBLE
 1810 - 020A	MODERN STONE*
 1810 - 021A	DARK LICHEN
 1810 - 022A	NIGHT SKY
 1810 - 023A	CHARISMATIC PINK
 1810 - 024A	CHEERS!
 1810 - 025A	VINTAGE LEATHER
 1810 - 026A	BLACK NOVEL*
 1810 - 027A	GOLDEN MUSTARD
 1810 - 028A	BOREAL GREEN
 1810 - 029A	DEEP SEA BLUE
 1810 - 030A	VIBRANT RED
 1810 - 031A	RASPBERRY WINE
 1810 - 032A	SPARKLING WHITE*
 1810 - 033A	ABSOLUTE BLACK*

#### Description

Premium eggshell finish paint with low volatile organic compound (VOCs) emissions. It contains no lead or mercury. It is super adherent, opaque, does not turn yellow, does not splatter and has light odour. This paint is ideal for walls with surface irregularities. It is very washable and scrub resistant.

#### Application

Shake the container well before applying the paint. Use a spatula to stir all the way to the bottom of the container. Apply with a synthetic fibre brush (polyester, nylon) and a good quality lint-free roller 0.5" (10 mm). For spray gun application, it is important to dilute the product 10-15 % with water to obtain a uniform application. Never apply below 50 °F (10 °C) and above 90 °F (32 °C). Humidity level should be lower than 50 %. Ventilate the room well. Two coats should be applied for best product performance.

#### Storage

Keep in a dry, well-ventilated place at a moderate temperature (about 68 °F (20 °C)). Avoid freezing.

\* Also available in pearl finish, ultra-washable. Ideal for doors & frames.

**Consult your municipality for proper disposal of leftover product. Keep out of the reach of children.**

#### Warning

Keep from freezing.

# MIX N'MATCH™

Pre-mixed Color Collection  
by Laurentide Paint

Laurentide Paint 



## 1810-033A - ABSOLUTE BLACK

### Mix N'Match Color Collection

100 % acrylic latex paint, interior, eggshell finish

#### Care instructions

It is best to use a soft cloth or sponge and a mild household soap. Do not use abrasive cleaners. Rinse off soap residue thoroughly. To achieve full performance of this paint wait at least 3-4 weeks before doing a first wash.

#### Surface preparation

Surface preparation is paramount and the final success of the project depends on it. All surfaces must be clean, dry and free of all traces of contaminants, mould and peeling paint. High gloss surfaces should be sanded to allow better adhesion of the paint. Remove old, peeling paint. Thoroughly clean the surface to be painted with a trisodium phosphate solution (TSP). Rinse well and leave to dry.

- **Bare wood:** Apply a bleed-proof latex primer for this purpose (pine, spruce, maple). It is important to seal the knots well. Some woods require the use of a product such as than Shellac on the knots.
- **New gypsum:** The plaster must be completely dry and clean before applying the paint. Apply the primer-sealer 1840-05A Prime3.
- **Previously latex-painted surfaces:** Apply a coat of latex primer 1840-05A Prime3.

- **Previously alkyd-painted surfaces:** If the existing alkyd coat has a matte finish, apply the latex primer 1840-05A Prime3, but if the finish is glossy, sand the surface to allow the latex primer to adhere.
- **New concrete and masonry:** Concrete must be completely dry before applying paint. Clean with muriatic acid and rinse well with water. Apply a coat of latex primer 1840-05A Prime3.
- **Metals:** Prepare the surface with a primer for metal, then apply paint according to application instructions.

**Note:** Do not use this paint on floors.

- <sup>1</sup> Drying may take longer in cold and humid conditions.

For more information and ideas, please contact our customer service or visit our stores/distributors. You can also visit our website at [mixnmatchpaint.com](http://mixnmatchpaint.com) or write to us at [info@laurentidepaint.com](mailto:info@laurentidepaint.com).

Before using this product, consult its Material Safety Data Sheet for the Use of Protective Equipment (Section 8), the Preventive Measures (Section 7) and Emergency First Aid Procedures (Section 4). The data mentioned above is provided by Laurentide Paint inc. for information purposes only and do not constitute in any way a representation, promise or warranty as to the use, duration or quality of the product. The identified product must be used in strict accordance with the specifications mentioned and any other instructions, warnings or guidelines issued by Laurentide Paint inc.