

MIX N'MATCH™

Laurentide Paint 



1870-0■■■AC

Ceiling Flat, Mix N'Match

100 % acrylic latex paint, interior-exterior, matte finish

Type	100 % acrylic
Gloss level	Maximum 2.5 % (60° & 85°)
Finish	Matte
Viscosity	90-100 K.U. ¹
Coverage	10 m ² /liter ; (107 ft ² /L)
Thinner / cleaner	Water
Format	3,78 L
Drying time	To the touch : 30-60 minutes ² To recoat : 3 to 5 hours
Concentration of solids	By volume : 50-60 % By weight : 50-60 %
VOCs	VOC-free < 5 g/l

Selection of Whites

- 1870 - 010AC JUST WHITE
- 1870 - 032AC SPARKLING WHITE

Description

Premium quality paint in matte finish paint. It contains no lead or mercury. This paint has zero VOCs (Volatile Organic Compounds). Ultra resistant and easy to apply. It has high opacity, is super adherent, non-yellowing and non-splattering. Ideal for ceilings with surface irregularities. It is not recommended for surfaces that require frequent washing due to its low sheen.

Cleaning of tools

Clean with soapy water.

Application

Shake the container well before applying the paint. Use a spatula to stir all the way to the bottom of the container. Apply with a synthetic fibre brush (polyester, nylon) and a good quality lint-free roller (13 mm). For spray gun application, it is important to dilute the product by 10% with water to obtain a uniform finish. Never apply below 10°C and above 32°C. Humidity level should be lower than 50%. Ventilate the room well. Two coats should be applied for best product performance.

Colour

This product should not be tinted in order to preserve its adhesion and sealing capabilities.

Storage

Keep in a dry, well-ventilated place at a moderate temperature (approx. 20°C). Keep from freezing.

Consult your municipality for proper disposal of leftover product. Keep out of the reach of children.

Warning

Keep from freezing.

Before using this product, consult its Material Safety Data Sheet for the Use of Protective Equipment (Section 8), the Preventive Measures (Section 7) and Emergency First Aid Procedures (Section 4). The data mentioned above is provided by Laurentide Paint inc. for information purposes only and do not constitute in any way a representation, promise or warranty as to the use, duration or quality of the product. The identified product must be used in strict accordance with the specifications mentioned and any other instructions, warnings or guidelines issued by Laurentide Paint inc.

MIX N'MATCH™

Laurentide Paint™

VOC^S
FREE

INTERIOR
EXTERIOR



1870-002AC

Ceiling Flat, Mix N'Match

100 % acrylic latex paint, interior-exterior, matte finish

Care Instructions

It is best to use a soft cloth or sponge and a mild household soap. Do not use abrasive cleaners. Rinse off soap residue thoroughly. To allow full performance of this paint, wait at least 3-4 weeks before doing a first wash.

Surface Preparation

Surface preparation is paramount, the final success of the project depends on it. All surfaces must be clean, dry and free of all contaminants and mould. High gloss surfaces should be sanded to allow better paint adhesion. Remove old, peeling paint. Thoroughly clean the surface to be painted with a solution of trisodium phosphate (TSP). Rinse well.

- **Bare wood:** Apply a coat of anti-bleeding latex primer (pine, spruce, cedar). It is important to seal the knots well. Some woods require the use of a product such as Shellac on the knots.
- **New gypsum:** The plaster must be completely dry and clean before applying the paint. Apply the primer-sealer 1840-005AC.
- **Previously latex-painted surfaces:** Apply the latex primer 1840-005AC.

- **Previously alkyd-painted surfaces:** If the existing alkyd coat has a matte finish, apply the latex primer 1840-005AC, but if the finish is glossy, sand the surface to allow the latex primer to adhere.
- **New concrete and masonry:** Concrete must be completely dry before applying paint. Wash with muriatic acid and rinse thoroughly. Apply the latex primer 1840-005AC.
- **Metals:** Prepare the surface with a primer for metal. Then, apply paint according to application instructions.

Note: Do not use this paint on floors.

- 1 Viscosity before colouring. Viscosity may vary depending on the base used.
- 2 Drying may take longer in cold and humid conditions.

For more information and ideas, please contact our customer service or visit our stores/distributors. You can also visit our website at mixnmatchpaint.com or write to us at info@laurentidepaint.com.

Before using this product, consult its Material Safety Data Sheet for the Use of Protective Equipment (Section 8), the Preventive Measures (Section 7) and Emergency First Aid Procedures (Section 4). The data mentioned above is provided by Laurentide Paint inc. for information purposes only and do not constitute in any way a representation, promise or warranty as to the use, duration or quality of the product. The identified product must be used in strict accordance with the specifications mentioned and any other instructions, warnings or guidelines issued by Laurentide Paint inc.